

Section 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name/ Trade Name: Orange Glo Wood Cleaner & Polish **HMIS**

> Ρ codes Н

> > 1 2 ND

Supplier: Orange Glo Manufacturer: Northern Labs

International 4701 Custer St PO Box 3998 Manitowoc WI 54221

Littleton, CO 80110 USA

Emergency Phone: 303-740-1909 MSDS preparation date: 14 September 2001

> L. Brown ChemTrec 800-424-9300 By:

Information Phone: 303-740-1909 14 September 2001 MSDS Revision date:

> MSDS Reviewed: 14 September 2001

Section 2: **COMPOSITION/INFORMATION ON INGREDIENTS**

General Description: Non-aerosol liquid wood cleaner and polish. Bitrex has been added to prevent

ingestion.

Hazardous Ingredients:

Ingredients not precisely identified are proprietary or nonhazardous

| CAS # | Chemical name | %'age range |
|------------|--|-------------|
| 64742-47-8 | Petroleum distillates, hydrotreated, light | 50-100 |
| 8028-48-6 | Cold pressed orange oil | <10% |
| | 1 | |
| | 1 | |

Section 3: **HAZARDS IDENTIFICATION**

General: Combustible. Repeated exposure may cause skin dryness or cracking

Emergency: Ingestion - seek immediate medical attention Primary Route(s) of Entry: Skin contact, eye contact, inhalation, ingestion

Respiratory tract irritation, headaches, dizzines, anesthesia, Effects of Overexposure-Inhalation: drowsiness, unconsciousness and other central nervous system

Effects of Overexposure-Minute amounts may be aspirated into lungs causing mild to severe

Ingestion: pulmonary injury

Effects of Overexposure-Eyes: Irritation

Effects of Overexposure-Skin: May cause drying and cracking of skin

Effects of Overexposure-Chronic Skin contact may aggravate an existing dermatitis

Hazards:

Section 4: **FIRST AID MEASURES**

Skin: Rinse well with warm water

Eyes: Rinse opened eyes with copious amounts of water. If irritation persists, call a

physician

Ingestion: Do not induce vomiting. Call a physician immediately.



• Inhalation: Remove to fresh air. If breathing is irregular or has stopped, administer oxygen and call a physician immediately

Section 5: FIRE FIGHTING MEASURES

Flashpoint and 170 deg F/76.4 deg Flammable limit: 1 Flammable limit: 6

method used: C (TCC) (LEL) (UEL)

Auto-ignition temperature: Product is not self igniting

Extinguishing media: Foam, dry chemical carbon dioxide, ABC type fire extinguishers

Special fire-fighting Self contained positive pressure breathing apparatus and protective clothing

protective equipment: should be worn

Unusual fire and explosion

hazards:

equipment:

Keep product away from ingitin sources, such as heat, sparks, pilot lights,

and open flames.

Explosion data: ND

Section 6: ACCIDENTAL RELEASE MEASURES

Personal protective In restricted areas, use approved chemical/mechanical filters designed to

remove a combination of particles and vapor. In confined area, use

approved air line type respirator or hood.

Material release or spill: Shut off and eliminate all ignition sources. Keep people away. Recover

free product. Add sand, earth or other suitable absorbent to spill area. Minimze breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourse, or extensive land areas.

Other: --

Section 7: HANDLING AND STORAGE

Storage: Store in original container. Do not store above 120 deg F.

Precautions during Ensure adequate ventilation during use. Avoid breathing vapors. Avoid skin

handling and storage: and eye contact. Keep out the reach of children and domestic animals.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits: Petroleum distillate OSHA PEL: NE (300 ppm recommended by supplier);

ACGIH TLV: NE

Orange Oil: OSHA PEL: not estab; ACGIH TLV: not estab

Engineering controls: To prevent fire or explosion risk from static accumulation and discharge,

effectively bond and/or ground product transfer system. Keep containers closed when not in use. Do not store near heat, sparks, flame or strong

oxidants.

Eye protection: None under normal use. Use splash goggles or face shield when eye

contact may occur



Protective clothing: None under normal use. Chemical resistant apron or other impervious

clothing if needed. Chemical resistant gloves if needed to avoid prolonged

or repeated skin contact.

Respiratory protection: Use supplied air respiratory protection in confined or enclosed spaces if

needed. Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations fo vapor in air. No smoking or use of flame or other ignition sources.

Other PPE: --

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Slightly viscous clear orange liquid

Odor: Orange Physical state: Liquid

Boiling point: 400 deg F/204 deg C

Vapor Pressure:NDVapor density:<7.3 (est)</th>Solubility in water:InsolubleEvaporation rate:< 0.01</td>

pH: NA Viscosity: 4.25 cSt @ 40 deg C

Melting point:NASpecific Gravity:8 lb/gal% volatile by volume:>90Cloud point:NDPartition coefficient:NDFreezing point:ND

Coefficient of water/oil ND

distribution:

Section 10: STABILITY AND REACTIVITY

Stability: Stable

Incompatibility: Strong oxidizers

Conditions to avoid: Application to hot surfaces, exposure to open flame Hazardous decomposition: Carbon monoxide, sulfur oxides, aldehydes, smoke

Hazardous polymerization: None

Section 11: TOXICOLOGICAL PROPERTIES

ND

Acute oral toxicity LD50 >5 g/kg Rat

Carcinogenicity: Not recognized as a carcinogen by ACHIG, IARC, NTP, OSHA

Reproductive toxicity/

Teratogenicity:

Mutagenicity: ND Toxicologically synergistic ND

products:

Section 12: ECOLOGICAL INFORMATION

Persistence and degradation: ND - product does not contain PCB's

Toxicity: ND

Other: Do not discharge into municipal sewers or waterways

Section 13: DISPOSAL CONSIDERATIONS

Disposal method: Dispose of in accordance with local, state and federal regulations Container disposal: Dispose of in accordance with local, state and federal regulations



Section 14: TRANSPORT INFORMATION

DOT proper shipping Not hazardous DOT technical name: NA

name:

DOT Hazard class: NA Hazard subclass: NA UN Number, proper NA Packing group: NA

shipping name:

Section 15: REGULATORY INFORMATION

TSCA: All ingredients are listed on the TSCA inventory

DSL: ND

OSHA Haz Com 29 CFR MSDS prepared pursuant to the Hazard Communication Standard (29

1910.1200: CFR 1910.1200)

WHMIS Classification: ND CERCLA and SARA: ND

Section 16: OTHER INFORMATION

% Volatile Organic <10%

Compounds (VOCs)

Legend: N.D. Not Determined N.E. Not Established N.A. Not Applicable

The information provided has been adapted from the manufacturer supplied MSDS.

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from use of MSDS information.



MSDS Addendum

Always follow label instructions and warnings. Typical use of product is a guideline only.

| Typical Use of | Used to clean and polish wood surfaces. NOT recommended for use on wood floors |
|----------------|--|
| Product: | due to risk of slip accidents. |